Considerations for Mass Timber in Defense Construction Projects

Moderator: Marc Jones, P.E. – VP Electrical Engineering, Professional Engineering Consultants (PEC)

Speakers:

- Zach Bowden, P.E. Structural Team Lead, PEC
- Karen Gesa, P.E. Technical Director, WoodWorks
- Pete Stynoski, Ph.D., Research Civil Engineer, US Army ERDC

May 14, 2024, 1:30 p.m.







MAY 14-16, 2024 **DRLANDO, FL**





or browse to jetc.cnf.io

This is an interactive session. To participate, use your mobile device: jetc.cnf.io Or scan the QR Code

- Find the session.
- The presenter will unlock the poll(s) during the presentation.
- Please complete a brief Evaluation Survey at the end of the session.

HOUSEKEEPING ITEMS

Take Note of Exits

Silence Your Mobile Devices

Presentations and Audio Recordings will be available in the Attendee Service Center until August 30, 2024


Download your PDH record in the Attendee Service Center before August 30, 2024






Opening Reception at Universal CityWalk

(Minimum age 18 - No Children)



Bring Your Name Badge with Drink Tickets) + Your ID



Get Your Wrist Band
TODAY at the
Registration Help Desk
or SAME Booth



Buses depart Gaylord & Caribe Royale, beginning at 6:00 p.m.

Thank You to our Education Session Sponsors











MODERATOR



Marc Jones, P.E. PEC

VP Electrical Engineering

- I'm a Kansas State Wildcat and Kansas City Chiefs fan.
- I love to vacation anywhere in the mountains.
- My hobbies include woodworking, gardening and A/V systems.



SPEAKER




Zach Bowden, P.E. PEC

Structural Team Lead

- Host of Structural Engineering podcast.
- Currently training for a 50k run.





Karen Gesa, P.E. WoodWorks Technical Director

- I have a flower farm in northern Virginia
- I'm a horse person and used to enjoy hunter/jumper before I got all old
- I have had many different foster and rescue animals including a mammoth mule





Pete Stynoski, Ph.D. US Army ERDC Research Civil Engineer

- Racecar designer, mechanic, and driver
- Rode four of the seven Giga Coasters
- Visited North Korea
- Superpower: Learning

Live Content Slide

Poll: Have you been involved with the design of a mass timber structure?

What is Mass Timber?






The second secon




Design of Mass Timber?

Panel Size and Efficiencies


- 8 12 ft wide X 40 60 ft long
- Grid spacing
- Limit waste
- Framing types

















Where to start?
















CROSS-







Mechanical / Electrical / Plumbing







Source: Alex Schreyer







Seismic Considerations

Codified Systems

- Concrete shearwalls (R = 2 8)
- Steel braced frame (R = 3 8)
- Light framed wood shear walls (R= 6.5 7)
- Steel moment frames (R = 3 8)
- Mass timber shearwalls (R = 1.5 4)













Live Content Slide

Poll: What is the main barrier keeping you from designing a mass timber project?

Code & Mass Timber

Model Building Code Acceptance

PRG-320

NDS



2015 International Building Code








TALL MASS TIMBER

2021 IBC Introduces 3 new tall wood construction types: IV-A, IV-B, IV-C Previous type IV renamed type IV-HT

BUILDING	IILDING TYPE I		TYPE II		TYPE III		TYPE IV			TYPE V		
ELEMENT	Α	В	Α	В	Α	В	Α	В	С	HT	Α	В

Tall Mass Timber: Up to 18 Stories in Construction Types IV-A, IV-B or IV-C



Fire Resistance

BUILDING CODE APPLICATIONS | FIRE RESISTANCE

Mass Timber's Fire-Resistive Performance is Well-Tested, Documented and Recognized via Code Acceptance




Table 16.2.1A **Char Depth and Effective Char** Depth (for $\beta_n = 1.5$ in./hr.)

Required Fire Resistance (hr.)	Char Depth, a _{char} (in.)	Effective Char Depth, a _{eff} (in.)				
1-Hour	1.5	1.8				
1½-Hour	2.1	2.5				
2-Hour	2.6	3.2				

Source: AWC's NDS



Inventory of Fire Tested MT Assemblies

Table 1: North American Fire Resistance Tests of Mass Timber Floor / Roof Assemblies



Mass Timber Panel	Manufacturer	CLT Grade or Timber Grade	Ceiling Protection	Panel Connection	Floor Topping	Load Rating	Fire Resistance Achieved	Source	Testing Lab
3-ply CLT (114mm 4.488 in)	Nordic	SPF 1650 Fb 1.5E MSR x SPF #3	2 layers 1/2" Type X gypsum	Half-Lap	None	Reduced 36% Moment Capacity	1	1 (Test 1)	NRC Fire Laboratory
3-ply CLT (105mm 4.133 in)	Structurlam	SPF #1/#2 x SPF #1/#2	l layer 5/8" Type X gypsum	Half-Lap	None	Reduced 75% Moment Capacity	1	1 (Test 5)	NRC Fire Laboratory
5-ply CLT (175mm 6.875")	Nordic	El	None	Topside Spline	2 staggered layers of 1/2" cement boards	Loaded, See Manufacturer	2	2	NRC Fire Laboratory March 2016
5-ply CLT (175mm 6.875")	Nordic	El	1 layer of 5/8" Type X gypsum under Z- channels and furring strips with 3 5/8" fiberglass batts	Topside Spline	2 staggered layers of 1/2" cement boards	Loaded, See Manufacturer	2	5	NRC Fire Laboratory Nov 2014
5-ply CLT (175mm 6.875")	Nordic	El	None	Topside Spline	3/4 in. proprietary gypcrete over Maxxon acoustical mat	Reduced 50% Moment Capactiy	1.5	3	UL
5-ply CLT (175mm 6.875")	Nordic	El	1 layer 5/8" normal gypsum	Topside Spline	3/4 in. proprietary gypcrete over Maxxon acoustical mat or proprietary sound board	Reduced 50% Moment Capactiy	2	4	UL
5-ply CLT (175mm 6.875")	Nordic	EI	I layer 5/8" Type X gyp under Resilient Channel under 7 7/8" I-Joists with 3 1/2" Mineral Wool beween Joists	Half-Lap	None	Loaded, See Manufacturer	2	21	Intertek 8/24/2012
5-ply CLT (175mm 6.875")	Structurlam	E1M5 MSR 2100 x SPF #2	None	Topside Spline	1-1/2" Maxxon Cyp-Grete 2000 over Maxxon Reinforcing Mesh	Loaded, See Manufacturer	2.5	6	Intertek, 2/22/2016
5-ply CLT (175mm 6.875")	DR Johnson	V1	None	Half-Lap & Topside Spline	2" gypsum topping	Loaded, See Manufacturer	2	7	SwRI (May 2016)
5-ply CLT (175mm 6.875")	Nordic	SPF 1950 Fb MSR x SPF #3	None	Half-Lap	None	Reduced 59% Moment Capacity	1.5	1 (Test 3)	NRC Fire Laboratory
5-ply CLT (175mm 6.875")	Structurlam	SPF #1/#2 x SPF #1/#2	1 layer 5/8" Type X gypsum	Half-Lap	None	Unreduced 101% Moment Capacity	2	1 (Test 6)	NRC Fire Laboratory
7-ply CLT (245mm 9.65")	Structurlam	SPF #1/#2 x SPF #1/#2	None	Half-Lap	None	Unreduced 101% Moment Capacity	2.5	l (Test 7)	NRC Fire Laboratory
5-ply CLT	Smart I am	SL-V4	None	Half-Lan	1/2" nlywood with 8d nails	Loaded,	2.	12	Western Fire Center

https://www.woodworks.org/resources/inventory-of-fire-resistance-tested-mass-timber-assemblies-penetrations/



Market Drivers

Tall Mass Timber: Structural Warmth is a Value-Add






Construction Impacts: Labor Availability





Photo: Lendlease

Construction Impacts: Schedule



ESTIMATED ENVIRONMENTAL **IMPACT OF WOOD USE**



Volume of wood products used: 2,233 cubic meters of CLT and Glulam



U.S. and Canadian forests grow this much wood in: 6 minutes



Carbon stored in the wood: 1,753 metric tons of CO.



Avoided greenhouse gas emissions: 679 metric tons of CO.



Total potential carbon benefit: 2,432 metric tons of CO.

THE ABOVE GHG EMISSIONS ARE EQUIVALENT



511 cars off the road for a year



Energy to operate a home for 222 years

*Estimated by the Wood Carbon Calculator for Buildings, based on research by Sathre,

and J. O'Connor, 2010, A Synthesis of Research on Wood Products and Greenhouse Gas Impacts, FPInnovations (this relates to carbon stored and avoided GHG).

*CO2 in this case study refers to CO2 equivalent

Mass timber appeal

Reduced embodied carbon

Brock Commons, Vancouver, BC





Mass Timber Appeal

MATERIAL MASS


75% lighter weight than concrete








Mass Timber: Structure Often is Finish







Photos: Baumberger Studio/PATH Architecture/Marcus Kauffman

PUBLIC REPORT



New York City Public Schools Mass Timber Design Feasibility Study

Submitted to:



NYC School Construction Authority 30-30 Thomson Avenue Long Island City, NY 11101

Prepared by:



EME Group 550 7th Avenue, 10th Floor New York, NY 10018

December 20, 2023

SPACE SAVINGS DUE TO USE OF MT	TYPE III-A*	TYPE IV-HT
GLT Columns	457.21	457.21
Exterior CLT Walls (Type IV-HT only)		325.50
Typical Classroom CLT Partitions	168.04	168.04
SPACE PENALTY DUE TO USE OF MT		
2-Hr and/or Acoustical CLT Partitions	-829.32	-674.27
TOTAL CHANGE IN USABLE GSF	-204.06	276.49
Percentage Change (from 40,510 GSF)	-0.5%	0.7%

^{*}See notes under Code Clarifications section above

Table 3. Space Savings of Mass Timber Construction at Addition

http://www.nycsca.org/Design/NYC-Green-Schools-Guide#GSG-Reference-Materials-154

PUBLIC REPORT



New York City Public Schools Mass Timber Design Feasibility Study

Submitted to:



NYC School Construction Authority 30-30 Thomson Avenue Long Island City, NY 11101

Prepared by:



EME Group 550 7th Avenue, 10th Floor New York, NY 10018

December 20, 2023

The following MT elements take up less space than their baseline counterparts:

- Exposed GLT columns vs. baseline reinforced concrete columns with GWB furring
- Classroom-to-classroom CLT partitions vs. baseline GWB stud walls
- Exterior CLT walls vs. baseline exterior stud walls (Type IV-HT construction only)

The following MT elements take up more space than on baseline counterpart:

- 2-hour rated and/or acoustical CLT partitions vs. baseline GWB rated stud walls
- This is one of the reasons why EME recommends the use of the baseline GWB stud wall design for 2-hr FRR and/or acoustical partitions instead of their CLT versions, in both the Type III and Type IV construction scenarios.



Candlewood Suites, AL

- Built by Lendlease
- 4-story hotel built on a military base pre-2018 using CLT floors, walls and roof
- CLT not considered conventional construction – so needed to meet blast and progressive collapse requirements
- Completed 37 percent faster than similar hotels
- Built with 44 percent fewer person-hours than similar hotels




https://www.woodworks.org/resources/constructionadvantages-sell-hotel-developer-on-mass-timber/



Current State of Mass Timber Projects


Through 2023 2,035 mass timber projects in design or have been constructed in the U\$




Sustainability

U.S. Forest Land:

Forest Area in the United States 1630 – 2017



State of our Forests: US Timber Volume on Timberland




■ North ■ South ■ West

Not including national parks and preserves – only timberland



New Buildings & Carbon Dioxide Emissions

Global CO₂ Emissions by Sector



Buildings generate 36% of annual carbon dioxide emissions

Operational carbon: 27%

Embodied carbon: 9%

Adapted from: UN environment programme Global Alliance for Buildings and Construction



Embodied Carbon


Building Energy Consumption

Manufacture, transport and installation of construction materials

Operational Carbon

Carbon Benefits of Wood

- Lower embodied carbon compared to other common building materials
- Less fossil fuel consumed during manufacture
- **Avoid process emissions**
- Extended carbon storage in products
- Carbon sequestration in forests
- Promotes forest health



Platte Fifteen Denver's First CLT Commercial Office Building


PROJECT DETAILS

LOCATION:

Denver, Colorado

SIZE:

Five stories; 150,418 square feet



Source: Platte Fifteen Life Cycle Assessment https://www.woodworks.org/resources/plattefifteen-life-cycle-assessment/

Rendering: Hickok Cole Architects














Figure 15. Comparison of the structural system GWP above the level two podium slab and the whole building cost of the three systems. Source: Platte Filted Life Gycle Assessment Hittps://www.woodworks.org/resources/platte-

Source: Platte Fifteen Life Cycle Assessment fifteen-life-cycle-assessment/



Protective Design

Protective Design Applied Research for Mass Timber

Blast

WoodWorks Blast Testing ISIEMS Test on 7-Ply CLT Panel **USACE PDC CLT Shock Tube Testing** U of Ottawa CLT Shock Tube Testing WoodWorks NLT Shock Tube Testing

Ballistic


Georgia Tech Ballistic Testing Reinforced CLT Development **Ballistic Testing** Quasi-Static Full-Size Panel Testing

Forced Entry

DOS Forced Entry Test

Progressive Collapse

Updates to the UFC 4-023-03 to include mass timber currently underway



Live Content Slide

Poll: How many Mass Timber DoD structures have you designed, built, operated from, or slept in?

Drivers (or Administrative Leadership Style)

- FY22 NDAA Sec. 2861 [Sustainable Materials Pilot Projects]
- EO 14008 [Tackling the Climate Crisis]
- EO 14057 [Decarbonization of the Federal Economy]
 - Buy Clean Task Force
- DODD 4715.21 [Climate Change Adaptation and Resilience]
- Joint Concept for Contested Logistics (JCL or JCCL)
 - Diversify Class IV (construction materials) supply chains
- Economic (LCCA) vs Environmental (LCI or LCA) factors
 - Proliferation of the Environmental Product Declaration (EPD)

Three Distinct Opportunities

Near-term and Mid-term goals:

- ✓ ECB directing consideration of Mass Timber
- Training and Guidance via Woodworks
- Criteria Change Request to update penetration equation (UFC 4-023-07)
- Progressive collapse experiments
- Custom reinforcement for signature reduction and max performance





'Light Frame' Designed for Disassembly

Anti-Terrorism / Force Protection









MILCON

5 CLT hotels operational via Privatization of Army Lodging (PAL) [Redstone, Drum, JBLM, Jackson]





ENGINEERING AND US Army Corps CONSTRUCTION BULLETIN

No. 2023-14

Issuing Office: CECW-EC

Issued: 20 Sep 23

Expires: 20 Sep 25

SUBJECT: Mandatory Consideration of Mass Timber in Army Military Construction (MILCON) and Civil Works Vertical Construction Projects

Directive and Policy **CATEGORY:**

- "...consider at least one option where mass timber is a substantial structural component..."
- "For example, the high bay areas of fire stations, hangars, and tactical equipment maintenance facilities may not be practical ... however, the administrative portions of these facilities may."
- "... justifications detailing why a mass timber structural system was or was not selected for the project must be included in the project Design Analysis..."
- "...if Mass Timber increases square footage beyond a Standard Design GSF limitation, the increase must be coordinated with the applicable COS..."

LendLease - CLT Privatized Army Lodging










Background



UNIFIED FACILITIES GUIDE SPECIFICATIONS

References are in agreement with UMRL dated January 2024

SECTION TABLE OF CONTENTS

DIVISION 06 - WOOD, PLASTICS, AND COMPOSITES

SECTION 06 18 00

GLUED-LAMINATED CONSTRUCTION

Manufacturers & Suppliers

Discover mass timber & light-frame projects

People & Companies



FEDERAL ENERGY MANAGEMENT PROGRAM

FEMP

SERVICES

REPORT

and connect with their project teams

Building Life Cycle Cost Programs

Department of Defense

Potential Usage in Military Construction of Cross-Laminated Timber (CLT) A Next Generation Mass Timber Construction System







National Standards, Local Codes


- ASCE 7-22 Chapter 12 Seismic Response
 - R Value modification
 - Higher Seismic Demand AND Less Efficient System
- IBC 2021 Revamped CLT Information in **Chapter 6 Building Types**
 - Unknown unknowns drive Type III-B
- NDS/AWC Special Design Provisions for Wind and Seismic
- Capacity Based Design for Shear Walls
 - Impact in Seismic Design Category C and D regions




2020 NEHRP Recommended Seismic **Provisions: Design Examples, Training Materials, and Design Flow Charts**

FEMA P-2192-V1/November 2021 Volume I: Design Examples












R&D – Environmental Resilience




R&D – Penetration Resistance

$$T_W = 9837 \left(\frac{v^{0.4113} w^{1.4897}}{\rho \left(\frac{\pi D^2}{4} \right)^{1.3596} H^{0.5414}} \right)$$








Nylon ECLT entry



Nylon ECLT exit



Carbon ECLT entry



Carbon ECLT exit



DFC ECLT entry




DFC ECLT exit



DFC ECLT fracture path

R&D – Penetration Resistance



Striking Velocity (m/s) TMWH 3P UMWH 3P TMWH 6P UMWH 6P TMWH 9P Velocity 008 Residual 200 Pig Striking Velocity (ft/s)

Partial penetration

Full perforation



US Army Corps of Engineers Engineer Research and

Development Center

Mitigation of GHG Emissions for DoD Construction Materials and Infrastructure 6.4 VEOT

Unified Facilities Criteria & Unified **Facilities Guide Specifications for** Sustainable Military Construction -Concrete, Asphalt, Wood, and Life Cycle Assessment Perspectives

Talbot B. Rueppel, Jerry M. Paris, Sadie E. Casillas, Brent Panozzo, Ernie Heymsfield, Meghan Fuhler, Allison Young, Peter B. Stynoski, Ben C. Cox, Annette L. Stumpf, Trevor J. Looney Matthew W. Glasscott, Robert D. Moser, Justin Smith

November 2023

Research

Engineer

Development



3.2.2 Unified Facilities Guide Specifications (UFGS)......79 3.2.3 Mass Timber & the International Building Code (IBC)86 3.4.1 Design for Disassembly and Durability......109 3.4.2 Strategic Sourcing of Mass Timber for Social & Systemic Economic Benefits 110 3.4.3 Building Construction and Performance......111 3.5.1 Lateral Load Optimization 114 3.5.2 Blast & Ballistics Optimization 114 3.5.3 Fire Resistance Optimization 115












Mitigation of Progressive Collapse

- UFC 4-023-03, ASCE/SEI 76-23
 - Govt-Private partnership for Criteria Change Request


Common MT Pitfalls:


- Brittle material, yet ductile connections
 - Insufficient bracing
 - Ignoring moisture effects
- Glulam beams generally enable longer spans
 - Leads to deformation control
- Load-bearing exterior walls not always avoidable
 - Result: CLT acts as Deep Beam

https://doi.org/10.1016/j.istruc.2024.106131












Mitigation of Progressive Collapse

Common strategies:


- Just make shorter MT buildings!
 - < 3 stories \rightarrow FSL I or II
 - CLT Report to Congress, pg. 1
 - At odds with economic first cost
- Alternate Load Path method
 - Tie Force method poses connection challenges
- Proper detailing of fully-restrained, moment-carrying connections
- Glulam or CLT panel cantilevers





Mitigation of Progressive Collapse

Further reading:

- Structural Robustness and Timber Buildings
 - Wood Material Science & Engineering 14(2) 2019
 - https://doi.org/10.1080/17480272.2018.144
- Prevention of Disproportionate Collapse for Multistory Mass Timber Buildings: Review of Current Practices and Recent Research
 - Journal of Structural Engineering 148(7) 2022
 - https://doi.org/10.1061/(ASCE)ST.1943-541X.0003377









Robust Design

Considerations for Mass Timber in Defense Construction Projects

THANK YOU

Please take a few minutes to complete a short survey about this session. Your feedback will help us improve future programming for JETC.





or browse to jetc.cnf.io



- Zach Bowden, <u>zach.Bowden@pec1.com</u>
- Karen Gesa, <u>karen.gesa@woodworks.org</u>
- Pete Stynoski, <u>peter.b.stynoski@usace.army.mil</u>